

2.1 Mega Pixel HD-SDI DOME CAMERA

1/3" progressive CMOS (Panasonic), 2.1 Megapixels
Full HD resolution : 1920x1080/30fps, 1280x720/60fps
Horizontal TVL : MORE THAN 1100TVL

SINCE 1991
SAMBO
SAMBO HITECH CO., LTD.

HD
SDI 1080



SD10SHM920V1F

WDR / 3D-DNR
Indoor Type
Varifocal Lens : 2.8-12mm DC IRIS, ICR
Mechanical True Day & Night Filter
Built-in OSD key
ACCE / Defog / Sens-up / WDR
2D&3D-DNR / DPC / HLC / BLC
Digital zoom (x62)
Dimension(mm) Φ (90+125)x83

HD
SDI 1080



SD10SHM920F

WDR / 3D-DNR
Indoor Type
Lens : 3.6mm MEGA Fixed Lens
Mechanical True Day & Night Filter
Built-in OSD key
ACCE / Defog / Sens-up / WDR
2D&3D-DNR / DPC / HLC / BLC
Digital zoom (x62)
Dimension(mm) Φ (90+125)x83

HD
SDI 1080



VD05SHM900

WDR / 3D-DNR
Outdoor Type
Lens : 3.6mm MEGA Fixed Lens
Mechanical True Day & Night Filter
OSD controller
ACCE / Defog / Sens-up / WDR
2D&3D-DNR / DPC / HLC / BLC
Digital zoom (x62)
Dimension(mm) Φ (60+92)x65
Water Proof

HD
SDI 1080



VDF05SHM900

WDR / 3D-DNR
Outdoor Type
Lens : 3.6mm MEGA Fixed Lens
Mechanical True Day & Night Filter
OSD controller
ACCE / Defog / Sens-up / WDR
2D&3D-DNR / DPC / HLC / BLC
Digital zoom (x62)
Dimension(mm) Φ (60+92)x65
Water Proof

HD
SDI 1080



SD08SHM900F

WDR / 3D-DNR
Indoor Type
Lens : 3.6mm MEGA Fixed Lens
Mechanical True Day & Night Filter
Built-in OSD key
ACCE / Defog / Sens-up / WDR
2D&3D-DNR / DPC / HLC / BLC
Digital zoom (x62)

HD
SDI 1080



SD08SHM900V1F

WDR / 3D-DNR
Indoor Type
Varifocal Lens
Mechanical True Day & Night Filter
Built-in OSD key
ACCE / Defog / Sens-up / WDR
2D&3D-DNR / DPC / HLC / BLC
Digital zoom (x62)

HD
SDI 1080



SVD10SHM920V1F

WDR / 3D-DNR
Outdoor Type
Varifocal Lens : 2.8-12/6-22mm DC IRIS, ICR
Mechanical True Day & Night Filter
Built-in OSD key
ACCE / Defog / Sens-up / WDR
2D&3D-DNR / DPC / HLC / BLC
Digital zoom (x62)
Dimension(mm) Φ (96.6+132.3)x118
Water Proof
-Option
DC12V/AC24V DUAL VOLTAGE
IR PASS FILTER

2.1 Mega Pixel HD-SDI IR DOME CAMERA

1/3" progressive CMOS (Panasonic), 2.1 Megapixels
Full HD resolution : 1920x1080/30fps, 1280x720/60fps
Horizontal TVL : MORE THAN 1100TVL

HD
SDI 1080



SD10SHI920V1F

WDR / 3D-DNR
Indoor Type
Varifocal Lens : 2.8-12/6-22mm DC IRIS, ICR
20 IR LEDs
Mechanical True Day & Night Filter
Built-in OSD key
ACCE / Defog / Sens-up / WDR
2D&3D-DNR / DPC / HLC / BLC
Digital zoom (x62)
Dimension(mm) Φ (90+125)x83

HD
SDI 1080



SD10SHI925F

WDR / 3D-DNR
Indoor Type
Varifocal Lens : 2.8-12/6-22mm DC IRIS, ICR
25 IR LEDs
Mechanical True Day & Night Filter
Built-in OSD key
ACCE / Defog / Sens-up / WDR
2D&3D-DNR / DPC / HLC / BLC
Digital zoom (x62)
Dimension(mm) Φ (90+125)x83



VD05SHI910

WDR / 3D-DNR
 Outdoor Type
 Lens : 3.6mm MEGA Fixed Lens
 10 IR LEDs
 Mechanical True Day & Night Filter
 OSD controller
 ACCE / Defog / **Sens-up / WDR**
 2D&3D-DNR / DPC / HLC / BLC
 Digital zoom (x62)
 Dimension(mm) Φ (60+92)x65
 Water Proof



VDF05SHI910

WDR / 3D-DNR
 Outdoor Type
 Lens : 3.6mm MEGA Fixed Lens
 10 IR LEDs
 Mechanical True Day & Night Filter
 OSD controller
 ACCE / Defog / **Sens-up / WDR**
 2D&3D-DNR / DPC / HLC / BLC
 Digital zoom (x62)
 Dimension(mm) Φ (60+92)x65
 Water Proof



SD08SHI924F

WDR / 3D-DNR
 Lens : 3.6mm MEGA Fixed Lens
 24 IR LEDs Mechanical True Day & Night Filter
 Built-in OSD key
 ACCE / Defog / **Sens-up / WDR**
 2D&3D-DNR / DPC / HLC / BLC
 Digital zoom (x62)



SD08SHI924V1F

WDR / 3D-DNR
 Varifocal Lens
 24 IR LEDs Mechanical True Day & Night Filter
 Built-in OSD key
 ACCE / Defog / **Sens-up / WDR**
 2D&3D-DNR / DPC / HLC / BLC
 Digital zoom (x62)



SVD10SHI920V1F

WDR / 3D-DNR
 Outdoor Type
 Varifocal Lens : 2.8-12/6-22mm DC
 IRIS, ICR
 20 IR LEDs
 Mechanical True Day & Night Filter
 Built-in OSD key
 ACCE / Defog / **Sens-up / WDR**
 2D&3D-DNR / DPC / HLC / BLC
 Digital zoom (x62)
 Dimension(mm) Φ (96.6+132.3)x118
 Water Proof

2.1 Mega Pixel HD-SDI STANDARD CAMERA

1/3" progressive CMOS (Panasonic), 2.1 Megapixels
 Full HD resolution : 1920x1080/30fps, 1280x720/60fps
 Horizontal TVL : MORE THAN 1100TVL



SHC900N

WDR / 3D-DNR
 Outdoor Type
 Mechanical True Day & Night Filter
 Built-in OSD key
 ACCE / Defog / **Sens-up / WDR**
 2D&3D-DNR / DPC / HLC / BLC
 Digital zoom (x62)
 Dimension(mm) 63x55x(L)120
 -Option
 CS MOUNT Lens 3-8mm
 CS MOUNT Lens 2.8-12mm
 AC95V-245V
 DC12V/AC24V DUAL VOLTAGE

2.1 Mega Pixel HD-SDI IR BULLET CAMERA

1/3" progressive CMOS (Panasonic), 2.1 Megapixels
Full HD resolution : 1920x1080/30fps, 1280x720/60fps
Horizontal TVL : MORE THAN 1100TVL



SNI920V1F

WDR / 3D-DNR
Outdoor Type
Varifocal Lens : 2.8~12mm DC IRIS,
ICR
20 IR LEDs
Mechanical True Day & Night Filter
Built-in OSD key
ACCE / Defog / **Sens-up / WDR**
2D&3D-DNR / DPC / HLC / BLC
Digital zoom (x62)
Dimension(mm) Φ 65x159.6
Water Proof
-Option
DC12V/AC24V DUAL VOLTAGE
Heater



SNI925F

WDR / 3D-DNR
Outdoor Type
Lens : 3.6mm Fixed Lens
25 IR LEDs
Mechanical True Day & Night Filter
Built-in OSD key
ACCE / Defog / **Sens-up / WDR**
2D&3D-DNR / DPC / HLC / BLC
Digital zoom (x62)
Dimension(mm) Φ 65x159.6
Water Proof
-Option
DC12V/AC24V DUAL VOLTAGE
Heater



SNHI940V1F

WDR / 3D-DNR
Outdoor Type
Varifocal Lens : 2.8~12/6~22mm DC
IRIS, ICR
40 IR LEDs
Mechanical True Day & Night Filter
Built-in OSD key
ACCE / Defog / **Sens-up / WDR**
2D&3D-DNR / DPC / HLC / BLC
Digital zoom (x62)
Dimension(mm) Φ 75x167.9
Water Proof
-Option
DC12V/AC24V DUAL VOLTAGE
Heater



SNI930V1F

WDR / 3D-DNR
Outdoor Type
Varifocal Lens : 2.8~12/6~22mm DC IRIS, ICR
30 IR LEDs
Mechanical True Day & Night Filter
Built-in OSD key
ACCE / Defog / **Sens-up / WDR**
2D&3D-DNR / DPC / HLC / BLC
Digital zoom (x62)
Dimension(mm) Φ 75x167.9
Water Proof
-Option
DC12V/AC24V DUAL VOLTAGE
Heater



SDI940V1F

WDR / 3D-DNR
Outdoor Type
Varifocal Lens : 6~50mm DC IRIS, ICR
40 IR LEDs
Mechanical True Day & Night Filter
Built-in OSD key
ACCE / Defog / **Sens-up / WDR**
2D&3D-DNR / DPC / HLC / BLC
Digital zoom (x62)
Dimension(mm) Φ 77x186
Water Proof
-Option
DC12V/AC24V DUAL VOLTAGE
Heater



2.1 Mega Pixel HD-SDI PTZ



SPHD230WE

32x Digital Zoom
HD-SDI and composite output
True D&N ICR
Endless 360° Pan Rotation, Pattern,
Swing and Group Functions
Dimension(mm) Φ 237x(H)310



2.1 Mega Pixel HD-SDI DVR



SSD04WH

HD-SDI 4CH
Video In : 4CH, Video Out : 1VGA, 1HDMI
Audio Input/Output : 4RCA / 1RCA
Recording Speed : 120fps@1080p
Recording Resolution : 1080p(1920*1080), 720p(1280*720)
VMS / Web Viewer / PDA / Smart Phone Viewer
Storage Device : 2 internal HDDs (up to 6TB)
Backup Device : External HDD, Memory Stick



SSD07WH

HD-SDI 7CH
Video In : 4CH, Video Out : 1VGA, 1HDMI
Audio Input/Output : 4RCA / 1RCA
Recording Speed : 210fps@1080p
Recording Resolution : 1080p(1920*1080), 720p(1280*720)
VMS / Web Viewer / PDA / Smart Phone Viewer
Storage Device : 2 internal HDDs (up to 6TB)
Backup Device : External HDD, Memory Stick



SSD16WH

HD-SDI 16CH (1080p, 1080i or 720p)
Video In : 16CH, Video Out : 1VGA, 1HDMI
Audio Input/Output : 8CH / 1CH
Recording Speed : 480fps@1080p(NTSC), 400fps@1080p(PAL)
Recording Resolution : 1080p(1920*1080), 720p(1280*720)
VMS / Web Viewer / PDA / Smart Phone Viewer
Storage Device : 4 internal HDDs (up to 12TB)
Backup Device : External HDD, Memory Stick, Internal ODD(option)



HD-SDI ACCESSORY

HD-SDI REPEATER



- 1 IN/2 OUT for HD-SDI distribution function
- Extending the transmission distance up to 200M (Full HD: 1.5G) over RG-6/U coaxial cable
- supporting SMPTE 292M / 424M Resolution
- LED Indication for HD-SDI signal and Power



HD-SDI CONVERTER

- HDMI Output resolution is selectable
- Long distance transmission over 200m (Full HD: 1.5G) / 130m (Full HD: 3G)
- Transmission distance extension function (Used as a repeater)
- Auto diagnosis of cable status for safe power supply
- Surge Protection function built-in transmitter